CLAIMS

1.   A device for use in acquiring address information at a link in a telecommunication network, the device comprising:

        a connection for the telecommunication network;

        a processing system operable to receive a data stream through the connection and determine the address information contained in the data stream based on the occurrence of a flag in a message signal unit (MSU) contained in the data stream;

        a display operatively connected to the processing system, the display operable to display the address information; and

        an arrangement for supplying power to the display and the processing system from a self-contained power source.

2.   The device of claim 1 wherein the address information comprises:

        an origination point code; and

        a destination point code.

3. The device of claim 2 wherein the processing system is further operable to determine an application part based on a specified field within the MSU, and wherein the display is further operable to display the application part.

1   4. The device of claim 2 wherein the MSU is a signaling system seven

2   (SS7) MSU.

1   5. Apparatus for use in acquiring address information at a link in a

2   telecommunication network, the apparatus comprising:

3   means for connection for the telecommunication network;

4   means for receiving a data stream through the means for

5   connection;

6   means for determining the address information contained in the data

7   stream based on the occurrence of a flag in a message signal unit (MSU)

8   contained in the data stream; and

9   means for displaying the address information, the means for

10   displaying operatively connected to the means for determining.

1   6. The apparatus of claim 5 further comprising means to determine and

2   display an application part.

1   7. A method of presenting address information at a link in a

2   telecommunication network, the method comprising:

3   receiving a data stream;

4   detecting the occurrence of a flag in the data stream, the flag

5   indicating a beginning of a message signal unit (MSU) contained within the

6   data stream;

7   collecting address bits based on a positioning of the address bits

8   within the MSU relative to the flag;

9   parsing the address bits to determine the address information; and

10   displaying the address information.

1   8.   The method of claim 7 wherein the parsing of the address bits is

2   accomplished at least in part by determining an origination point code and a

3   destination point code contained within the address information.

1   9. The method of claim 8 further comprising:

2   collecting application part bits from a specified field within the MSU;

3   determining an application part based on the application part bits;

4   and

5   displaying the application part.

1   10.   The method of claim 8 wherein the MSU is a signaling system seven

2   (SS7) MSU.

1   11. Apparatus for presenting address information at a link in a

2   telecommunication network, the apparatus comprising:

3   means for receiving a data stream;

4   means for detecting the occurrence of a flag in the data stream, the

5   flag indicating a beginning of a message signal unit (MSU) contained within

6   the data stream;

7   means for collecting address bits based on a positioning of the

8   address bits within the MSU relative to the flag;

9   means for parsing the address bits to determine the address

10   information; and

11   means for displaying the address information.

1   12. The apparatus of claim 11 further comprising:

2   means for collecting application part bits from a specified field within

3   the MSU;

4   means for determining an application part based on the application

5   part bits; and

6   means for displaying the application part.